

Excellent Wall Filling



Storage

The product must be stored in accordance to the national regulations. The product should be kept in a well-ventilated place, protected from heat and direct sunlight. The containers must be kept tightly closed.

Handling

Handle with care. Stir well before use.

Packing

3.64 Ltr
14.56 Ltr

Health and Safety

While applying paint, wear appropriate eye protection. In case of eye contact with product, rinse with plenty of water for at least 15 minutes. Keep away from ignition sources because it is flammable. The container should be protected from extreme hot and cold temperature. Remove as much paints as possible from brushes and rollers before cleaning. Don't breathe spray mist or dust. Ensure proper ventilation when applying paint. When empty, don't use its container for edible storage. Place out of reach of the children. In case of any emergency, undergo medical supervision as soon as possible. It should be properly closed and kept in an upright position after use.

Description

Promax Wall Putty is ready to use, high-quality putty for filling crack & holes on interior masonry surfaces and patching up surface imperfections on plastered walls, wood hardboard & chipboard. It is specially formulated to form an ideal base to give a smooth finish for water-based paints.

Excellent Wall Filling

Promax Wall Putty - Acrylic Based is a water-based, ready to use putty which provides a strong and smooth foundation for a perfect paint finish. It is a technologically advanced product that has excellent filling and binding properties. It dries quick and leaves behind a super smooth surface ready for the application of a topcoat.

Product Information

Colours	White
Vehicle Type	Acrylic
Solids (Vol %)*	53 ± 2
No of coats	2
Specific Gravity	1.60-1.70
Stability of thinned paint	To be used within 45 mins




Recommended Use

Specially formulated to fill pores and imperfections of plaster, concrete and gypsum surfaces and wood surfaces. Specifically made for interior and exterior surfaces which give smooth, easy to apply and an ideal finish for successive coats.

Film Thickness and Spreading Rate

Dry film thickness	100-300 microns
Theoretical Spreading Rate	5-7(m ² / kg) Coat

Application Data

Application Method	Putty Knife  Trowel  Scraper 
Thinner/Cleaner	Clean water
Thinning	Not Required

Drying Time

Temperature	Dry to touch	Dry to handle	Recoating Time
25°C	2 Hours	4 Hours	4 Hours
35°C	1 Hours	3 Hours	3 Hours

Typical Paint System

Promax Primer Sealer Undercoat	1-2 Coat
Promax Excellent Wall Filling	1- 2 Coat
Promax Emulsion Topcoat	2- 3 Coat

