

## Superior Wall Emulsion



### Storage

The product must be stored in accordance to the national regulations. The product should be kept in a well-ventilated place, protected from heat and direct sunlight. The containers must be kept tightly closed.

### Handling

Handle with care. Stir well before use.

### Packing

0.91 Ltr  
3.64 Ltr  
14.56 Ltr

### Health and Safety

While applying paint, wear appropriate eye protection. In case of eye contact with product, rinse with plenty of water for at least 15 minutes. Keep away from ignition sources because it is flammable. The container should be protected from extreme hot and cold temperature. Remove as much paints as possible from brushes and rollers before cleaning. Don't breathe spray mist or dust. Ensure proper ventilation when applying paint. When empty, don't use its container for edible storage. Place out of reach of the children. In case of any emergency, undergo medical supervision as soon as possible. It should be properly closed and kept in an upright position after use.

## Description

A specially formulated Superior Wall Emulsion with dependable performance for a long time. It gives unmatched durability and a smooth finish that has no equal in the Distemper Paint category and ensures shade retention for a long time. The easy application brings consistent finish for the years to come.

## Superior Wall Emulsion

Say goodbye to distemper and welcome emulsion finish. Give your home interior walls a smooth water-based emulsion paint finish with the Superior Wall Emulsion.

## Product Information

Colours	Standard Colour Range
Vehicle Type	Silicone
Solids (Vol %)*	42 ± 2
No of coats	2-3 Coats
Specific Gravity	1.40-1.50
Stability of thinned paint	To be used within 6-8 hours

## Recommended Use

Specially recommended for the exterior walls including plaster, concrete, gypsum, brickwork and exterior surfaces, where better finish than distemper is required.

## Film Thickness and Spreading Rate

Dry film thickness	15-23 microns $\mu$
Theoretical Spreading Rate	12-14(m <sup>2</sup> /l)

## Application Data

Application Method	Spray	Brush	Roller
Thinner/Cleaner	Clean Water		
Thinning	50-70%		

## Drying Time

Temperature	Dry to touch	Dry to handle	Recoating Time
25 °C	30 Minutes	2 hours	3 hours
35 °C	15 Minutes	1 hours	2 hours

## Typical Paint System

Promax Primer Sealer Undercoat	1-2 Coat
Promax Excellent Wall Filling	1- 2 Coat
Promax Superior Wall Emulsion	2- 3 Coat

