

Classic Plastic Emulsion



Storage

The product must be stored in accordance to the national regulations. The product should be kept in a well-ventilated place, protected from heat and direct sunlight. The containers must be kept tightly closed.

Handling

Handle with care. Stir well before use.

Packing

0.91 Ltr
3.64 Ltr
14.56 Ltr

Health and Safety

While applying paint, wear appropriate eye protection. In case of eye contact with product, rinse with plenty of water for at least 15 minutes. Keep away from ignition sources because it is flammable. The container should be protected from extreme hot and cold temperature. Remove as much paints as possible from brushes and rollers before cleaning. Don't breathe spray mist or dust. Ensure proper ventilation when applying paint. When empty, don't use its container for edible storage. Place out of reach of the children. In case of any emergency, undergo medical supervision as soon as possible. It should be properly closed and kept in an upright position after use.

Description

Promax Classic Plastic Emulsion is high-performance acrylic-based paint specifically made to provide premium finish to your walls. Thoughtfully designed to provide superior performance and application properties, it delivers exceptional flow and levelling with great coverage.

Acrylic-Binder Product

Classic Plastic Emulsion has a smooth and stylish matt finish, making it an ideal choice for our premium customers. It has twice the durability of distemper and is suitable for a wide variety of surfaces.

Product Information

Colours	Standard Colour Range
Vehicle Type	Silicone
Solids (Vol %)*	43 ± 2
No of coats	2-3 Coats
Specific Gravity	1.40-1.60
Stability of thinned paint	To be used within 6-8 hours

Recommended Use

Specially recommended for the interior walls including plaster, concrete, gypsum, brickwork and interior surfaces, where fine finishing and high scrub resistant finish is required.

Film Thickness and Spreading Rate

Dry film thickness	15-30 microns μ
Theoretical Spreading Rate	12-14(m ² /l)

Application Data

Application Method	Spray	Brush	Roller
Thinner/Cleaner	Clean Water		
Thinning	50-70%		

Drying Time

Temperature	Dry to touch	Dry to handle	Recoating Time
25 °C	30 Minutes	2 hours	3 hours
35 °C	15 Minutes	1 hours	2 hours

Typical Paint System

Promax Primer Sealer Undercoat	1-2 Coat
Promax Excellent Wall Filling	1- 2 Coat
Promax Classic Plastic Emulsion	2- 3 Coat

